	Lafarge
TectorAdmix	TectorAdmix
1200 Waterproof Ultra	1200 Waterproof Ultra () Sector
Waterprod Ør Develor Brigge waterprof Ør Performance Brigge waterprof Owner Owner	Horizon parka Hamiltonia parka Hamilto

TECTOR ADMIX - WATERPROOF

Description

Tector Admix is a high quality, water repellent powder admixture used for water and damp proofing in Mortars like plasters/renders, screeds and concrete applications

Use/Application

Suitable for Mortar and Concrete applications and mainly applied;

- In interior and exterior Plasters and screeds.
- In wet volumes such as bathroom, kitchen, balcony etc.
- In basements, cesspools, foundations, curtain walls,
- In water and waste water tanks, water treatment plant, swimming pools.

Benefits

Easy to Apply, Affordable and highly effective

Technical Data: WDUS 2274	
Content	Active chemical content special powder
Colour	Grey
Appearance	Powder
Density	0.50 kg/lt
Application	
Temperature	+5°C to +35°C

How to Apply

Fresh cement and TECTOR ADMIX must be mixed firstly. Then, sand aggregate are poured into the powders. Water is slowly added into the powder mixture and mixed until homogenous mixture is obtained.

Mixing

1 bag Cement (50kg) require 1 package (1kg) TECTOR ADMIX

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight. Shelf life 12 months in original unopened package.